

2017 ROCKFORD SPEEDWAY RULES AMENDMENTS (updated Feb 24 2017)

LATE MODELS

Dart Head part # 10110010 thru 10220010
Dart Iron Eagle 180 sbc 23* cyl head
LS Engines must have a chip, 7600 max RPM
No carbon fiber components of any kind
Oberg fuel shut off is optional

SPORTSMAN

In 2018, engine setback will be measured off center line of spindle with Referee as measurement tool.

AMERICAN SHORT TRACKERS

NO BUMP STOPS ALLOWED

BANDITS

No JDM motors. No Nissan VVL Motors. Motor must be available in make and model for vehicles produced in the United States.
2" hole in bell housing required
Front hoops allowed and may be connected to the strut/shock towers. Strut/shock towers may not be altered but can be connected to the front hoop bars and connected side to side.

ROADRUNNER

CARBURETOR

Stock unaltered 500 CFM Stock Holley 4412 2 bbl. or 1.375" Rochester allowed on all cars.
No alterations except removal of choke "Butterfly" allowed.
Double return springs required.
No Holley Ultra XP Carburetors allowed.
Carburetor Rework Guidelines:
A. Body of Carbs:
1. No polishing, grinding, or drilling of holes allowed.
2. Gasket surfaces may be machined for improved sealing.
B. The choke may be removed, but all screw holes must be permanently sealed.
C. Choke horn may not be removed.
D. Boosters may not be changed. Height, size, and shape must remain standard and unaltered.
E. Venturi area must not be altered in any manner. Casting ring must not be removed.
F. Base plate must not be altered in shape or size.
G. Butterflies: Stock butterflies must not be thinned or tapered. Idle holes may be drilled in butterflies. Screw ends may be cut even with shafts, but screw heads must remain standard.
H. Throttle Shafts: Shafts must remain standard and must not be thinned or cut in any manner.
I. Any attempt to pull outside air other than straight down through the venture is not permitted.
J. Jets may be changed. No dial-a-jet devices.
K. No addition of any material, such as epoxy, may be added to carb or parts except to seal vacated external screw holes.

**** Carb adaptor max 1" Part number 023-108 (Lefthander)**

FIGURE 8

Tires- Any street tire or Hoosier 850

V-6 cars (Original Sixers) allowed to race with proper roll cage and safety

GENERAL RULES

Protest fees will start at \$550

No Bump Stops allowed in any division

3.17 No E 85 Fuel Allowed. Fuel must meet properties of track pump fuel.

Fuel samples may be taken at ANY TIME and tested (digitron, specific gravity, germaine drop testing, water testing and any other testing deemed necessary). Alcohol, nitro methane, nitro propane, nitrous oxide, other oxygenating agents, other additives and/or fuels that contain masking agents or oxygen are NOT permitted. USE OF SUCH SUBSTANCE OR ADDITIVE WILL RESULT IN IMMEDIATE DISQUALIFICATION.